

## COLOURS/ DESIGNS



Closed -  
Solid Top



Open -  
With Holes

## APPLICATIONS

- Ideal for food areas, around machinery, packing areas, wet areas, repair garages

## FEATURES

- Approx. 24mm thick
- Heavy duty, durable design
- Great anti-slip grit coarse on the surface
- Modular design, interlocking to cover large areas
- Available with or without holes
- Edge ramps available to eliminate trip hazards
- Made from recycled material
- UV protected
- Indoor/outdoor use



Anti-Fatigue



ECO



Inter-Locking



Drainage



Outdoor Use



Indoor Use



Approx.  
Thickness

\*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
<b>MATERIAL</b>			
	Polymer	PVC	
	Colour	Black	
	Standard Sizes (mm)	500 x 500	
	Thickness (mm)	24	
	Weight (kg)	3.66 - Closed 2.94 - Open	
	Surface Finish	Grit solid top (Closed), Grit with holes (Open)	
	Backing Finish	Cleated	
<b>MECHANICAL</b>			
	Hardness	78 Shore	
	ADA Compliance	Yes	
	Co-Efficient of Friction	Wet - .69 Dry - .92-.96	
	Fire Exposure	Passed	
	UV Stabilised	Yes	
<b>TEMPERATURE</b>			
	Temperature Range	-30°C to +60°C	
<b>CHEMICAL RESISTANCE</b>			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	

## KEY:



POOR



FAIR



EXCELLENT

